

PRODUCT-INFO

ESSENTIAL COMPONENTS
FOR THE PROFESSIONAL

RG4.0

Bosch introduces its FIRST recovery machine – with competitive recovery rates on all refrigerants (included A2L). With an 1/2 HP / 1750 rpm motor – this design provides better recovery throughout, in all conditions. Packaged in the recognisable Bosch housing the RG4.0 out-performs all competitors, but remains lightweight and compact. The RG4.0 will meet your needs now, and those in the future.

- **Suitable for A2L refrigerants such as R32**

Refrigerants	R32, R-1234YZ, R-1234ZE, RRR12, R22, R134A, R401A, R401B, R401C, R402A, R402B, R404A, R406A, R407A, R407B, R407C, R407D, 408A, R409A, R410A, R411A, R411B, R412A, R417A, R422A, R422D, R427A, R500, R502, R507, R509 and others
---------------------	---



Recovery Rates (tested to UL standards)		R410A	R22	R134a
	Liquid Capacity, max push pull: (kg/hr)	410.5	367.62	306.24
	Liquid recovery rates: (kg/hr)	122.1	199.46	103.62
	Vapour recovery rates: (kg/hr)	10.7	9.90	7.26

- **Available in both 110v and 220v**

Product codes	240v – S070291GB 110v – S070290GB
----------------------	--------------------------------------

Compressor	Single cylinder 1/2 HP, 1700 / 1750 rpm (110) 1/2 HP, 1400 / 1450 rpm (240)
-------------------	---

Voltage	240V 50-60 Hz or 110V 50-60 Hz/250W
----------------	--

Fuse	12A (110) 8A (240)
-------------	--------------------

- **Maximum operating pressure of 38.5 bar / 550 psi**

High Pressure Cut Out	550 psi / 38.5 bar
------------------------------	--------------------

Distributed by
advanced engineering
World-leading products for air conditioning and refrigeration professionals



BOSCH

