

Schlösser Möller Kulde A/S Postboks 65 Bryn 0611 Oslo Norway	Your order B115517	
	Our reference 131128	Packing slip / Date PS534933 2.4.2020
	Your reference Lasse Djupvik	

Item	Product , Grade and Size			
007	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 12,7 (1/2)X0,89 MM X 5 M Nitrogenfyllda	1027.30	Kg	PU131128.7
		3480.00	M	
008	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 15,88 (5/8)X1,02 MM X 5 M Nitrogenfyllda	1317.54	Kg	PU131128.8
		3095.00	M	
009	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 19,05 (3/4)X1,07 MM X 5 M Nitrogenfyllda	510.58	Kg	PU131128.9
		945.00	M	
010	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 22,23 (7/8)X1,14 X 5 M Nitrogenfyllda	476.02	Kg	PU131128.10
		705.00	M	

According to: EN 12735-1

Mechanical properties

Item	Tensile strength R _m N/mm ²	0.2 % proof strength R _{p0.2} N/mm ²	Elongation %	Hardness	Grain size mm
007	465	440	A5 9		
008	459	431	A5 8		
009	460	424	A5 10		
010	460	428	A5 7		

Chemical composition %
 Cu-DHP/CW024A
 Cu min 99,90
 P 0,03

EDDY CURRENT TESTED:100%

Electrical conductivity at 20 ° C % IACS (mass), annealed

We hereby certify, that the material described above complies with the order.

These products have been produced under a certified Quality System
 ISO 9001: 2015 / DNV Certificate No.80561-2010-AQ-FIN-FINAS

Teemu Pihl

This document has been printed out through electrical mail.
 A copy with original signature is available in our factory.

Cupori Oy

P.O. Box 60, FIN-28101, Pori, Finland
 Tel. +358 2 511 4111, Fax +358 2 511 4002
 Domicile: Pori, Finland. Business ID 2639859-8, VAT FI26398598

Schlösser Möller Kulde A/S Postboks 65 Bryn 0611 Oslo Norway	Your order B115517	
	Our reference 131128	Packing slip / Date PS534933 2.4.2020
	Your reference Lasse Djupvik	

Item 011	Product , Grade and Size Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 53,98(2 1/8)X1,78 MM X 5 M Nitrogenfylda	365.40 Kg 140.00 M	PU131128.11
-------------	-------------------------------------------------------------------------------------------------------------------------------	-----------------------	-------------

According to: EN 12735-1

Mechanical properties

Item	Tensile strength R _m N/mm ²	0.2 % proof strength R _{p0.2} N/mm ²	Elongation %	Hardness	Grain size mm
------	------------------------------------------------------	-------------------------------------------------------------	-----------------	----------	------------------

011	374	349	A5	6	
-----	-----	-----	----	---	--

Chemical composition %
 Cu-DHP/CW024A
 Cu min 99,90
 P 0,03

EDDY CURRENT TESTED:100%

Electrical conductivity at 20 ° C % IACS (mass), annealed

We hereby certify, that the material described above complies with the order.

These products have been produced under a certified Quality System
 ISO 9001: 2015 / DNV Certificate No.80561-2010-AQ-FIN-FINAS



Teemu Pihl

This document has been printed out through electrical mail.
 A copy with original signature is available in our factory.

Cupori Oy

P.O. Box 60, FIN-28101, Pori, Finland
 Tel. +358 2 511 4111, Fax +358 2 511 4002
 Domicile: Pori, Finland. Business ID 2639859-8, VAT FI26398598