

Schlösser Möller Kulde A/S Postboks 65 Bryn 0611 Oslo Norway	Your order B115157	
	Our reference 130737	Packing slip / Date PS534571 6.3.2020
	Your reference Lasse Djupvik	

Item	Product , Grade and Size			
004	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 12,7 (1/2)X0,89 MM X 5 M Nitrogenfyllda	717.34 Kg 2430.00 M		PU130737.4
005	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 15,88 (5/8)X1,02 MM X 5 M Nitrogenfyllda	808.83 Kg 1900.00 M		PU130737.5
006	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 19,05 (3/4)X1,07 MM X 5 M Nitrogenfyllda	486.27 Kg 900.00 M		PU130737.6
007	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 22,23 (7/8)X1,14 X 5 M Nitrogenfyllda	634.69 Kg 940.00 M		PU130737.7

According to: EN 12735-1

Mechanical properties

Item	Tensile strength R _m N/mm ²	0.2 % proof strength R _{p0.2} N/mm ²	Elongation %	Hardness	Grain size mm
004	447	417	A5 9		
005	465	433	A5 8		
006	456	423	A5 8		
007	463	433	A5 9		

Chemical composition %

Cu-DHP/CW024A
 Cu min 99,90
 P 0,03

EDDY CURRENT TESTED:100%

Electrical conductivity at 20 ° C % IACS (mass), annealed

We hereby certify, that the material described above complies with the order.




Essi Tuovinen

This document has been printed out through electrical mail.
 A copy with original signature is available in our factory.

These products have been produced under a certified Quality System
 ISO 9001: 2015 / DNV Certificate No.80561-2010-AQ-FIN-FINAS

Cupori Oy

P.O. Box 60, FIN-28101, Pori, Finland
 Tel. +358 2 511 4111, Fax +358 2 511 4002
 Domicile: Pori, Finland. Business ID 2639859-8, VAT FI26398598

Schlösser Möller Kulde A/S Postboks 65 Bryn 0611 Oslo Norway		Your order B115157			
		Our reference 130737	Packing slip / Date PS534571 6.3.2020		
		Your reference Lasse Djupvik			
Item	Product , Grade and Size				
008	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 28,58 (1 1/8)X 1,27 MM X 5 M Nitrogenfylda	404.25 Kg	415.00 M	PU130737.8	
009	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 34,93(1 3/8)X1,4 MM X 5 M Nitrogenfylda	428.35 Kg	325.00 M	PU130737.9	
According to: EN 12735-1					
Mechanical properties					
Item	Tensile strength R _m N/mm ²	0.2 % proof strength R _{p0.2} N/mm ²	Elongation %	Hardness	Grain size mm
008	451	419	A5 7		
009	425	415	A5 4		
Chemical composition %					
Cu-DHP/CW024A					
Cu min 99,90					
P 0,03					
EDDY CURRENT TESTED:100%					
Electrical conductivity at 20 ° C % IACS (mass), annealed			We hereby certify, that the material described above complies with the order.  Essi Tuovinen <small>This document has been printed out through electrical mail. A copy with original signature is available in our factory.</small>		
These products have been produced under a certified Quality System ISO 9001: 2015 / DNV Certificate No.80561-2010-AQ-FIN-FINAS					

Cupori Oy

P.O. Box 60, FIN-28101, Pori, Finland
 Tel. +358 2 511 4111, Fax +358 2 511 4002
 Domicile: Pori, Finland. Business ID 2639859-8, VAT FI26398598